

ARTIST 03

Spray Adhesive



DAEHEUNG CHEMICAL

Artist 03 is a strong and quick tack adhesive formulated to bond fabric, paper, cardboard, leather, foil, fiberglass to itself and to metal, wood and a variety of other substrates.

1. Uses

- Bonding fabric, paper, cardboard, leather, foil, fiberglass.

2. Characteristics

- Spray pattern is a fine spray.
- Low soak-in, ideal for low porous surface.
- Strong adhesion.
- High coverage.
- The fan-type spray tip is available.

3. Physical properties

| Properties | Value |
|-----------------|---|
| Main component | Synthetic resin and styrene-butadiene copolymer mixture |
| Color | Yellowish-beige color. |
| Odor | Solvent odor when wet, None when dry |
| Solvents | Hexane |
| Solid contents | 25±1 % |
| Bonding time | 10 sec ~ 15 min |
| Use temperature | 5 ~ 50 °C |
| Flammability | Extremely flammable |
| Shelf life | 9 months in unbroken package under dry and cool condition |

4. How to use

- Shake container well before using.
- Spray out 15 to 20 cm apart from surface.
- For optimum performance, use between 15~30 °C.
- After application, it is dried for 10 seconds
- Joint and press then tightly.

5. Caution

- Read precaution on label before using.
- Avoid direct rays of the sun and keep in cool and dry place.
- Keep out of reach of children.
- Keep it away from the fire.(Further information : Extremely flammable. Keep away from spark, flame or heat)
- Ventilation the room well because of containing solvent.
- Don't use except for the original purpose.

6. Packaging

- 320g Spray C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,
Gyeonggido, Korea

Telephone +82-2-554-8211, +82-31-668-1424

Facsimile +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL