# **D-1000B**

Caulking Agent



D-1000B is a synthetic rubber base sealing adhesive, which is excellent in sealing, adhesion, water proof of construction and general industry. It is easily applied with conventional and without special equipment.

## 1. Uses

- For sealing joint in metal, glass, wood, aluminum, concrete and joints between various combinations of surface.
- For sealing expansion joints in ceramic tiled walls.
- Sealing adhere around bath and other fittings.

#### 2. Characteristics

- Excellent adhesive for water proof and sealing adheres to metal, glass, plastics, wood, and many other materials
- Easy handing property, as one component tube and can package type.

## 3. Physical properties

Properties	Value
Main component	Chloroprene rubber
Solvents	Toluene & mixed solvents
Color	Black paste
Solid contents	62±2 % (at 105±5 ℃ × 3hr)
Viscosity	90,000~100,000 cps (at 20 °C, RION VT-04 #2)
Specific gravity	1.20±0.10 g/cm³ (at 20 ℃)
SLUMP	Max. 10m/m (KS-F-4910)
Shelf life	9 months in unbroken package under dry and cool condition

#### 4. How to use

- Remover all dirt, grease, water and rust from the surface before applying.
- Likewise, the surfaces of the joints, gaps and crack must be dry and dust free.
- Open the cap of the sealing adhesive applies it to gaps, crack, and joints by pressing it with the hand or motor able method.

Applying amount: 400~600 g/m²

## 5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Keep out of reach of children.
- Keep it away from the fire.
- Ventilation the room well because of containing solvent.
- Close the cap tightly after using it
- Don't use except for the original purpose.

# 6. Packaging

• 18kg C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

# DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggi-do, Korea

**Telephone** +82-2-554-8211, +82-31-668-1424 **Facsimile** +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr

