

D-2000IP

Styrofoam adhesive

**DAEHEUNG CHEMICAL**

D-2000IP is modified vinyl acetate polymer base adhesive of the paste type, which is excellent in initial bonding strength, good durability and excellent adhesion to porous materials. This adhesive is used to bond the polystyrene foam, wood, concrete and gypsum board for construction.

1. Uses

- Wood, PW, polystyrene foam, concrete, gypsum board, insulation etc.

2. Characteristics

- Quick setting and excellent in initial and final bonding strength.
- Excellent in heat resistance and water resistance.
- Adhesion for porous materials.
- Good workability.

3. Physical properties

Properties	Value
Main component	Modified vinyl acetate
Color	Dark gray paste
Solid contents	73±2 % (at 105±5℃ x 3hr)
Viscosity	100,000~110,000 cps (at 25℃, RION VT-04 #2)
Solvent	Alcohol & mixed solvents
Open time	2~5 min (at 20℃)
Shelf life	9months in unbroken package under dry and cool condition

4. How to use

- Remove all dirt, grease, water and rust from the bonding surface before applying.
- Coating adequate amount of adhesive by brush or spatula and then joint them.
- Press with hand roller or other mechanical system.

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place
- Ventilation the room well because of containing solvent.
- Keep out of reach of children.
- Close the cap tightly after using it.
- Store at room temperature(5~25℃).
- Don't use except for the original purpose.

6. Packaging

- 15kg Tin C/N
- 10kg, 15kg, 20kg PE C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,
Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-663-5251

Facsimile +82-2-554-8215, +82-31-664-3361

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL